

镜头兼容性 Lens Compatibility	E-mount lenses								
	α9Ⅱ	α7RⅤ	α7Ⅳ	α7Ⅲ	α7CR	α7CⅡ	α7C	α6700	α6400
机型名称 Model Name	ILCE-9M2	ILCE-7RM5	ILCE-7M4K 40 FOCUS	ILCE-7M3K 40 FOCUS	ILCE-7CR 	ILCE-7CM2L 40 FOCUS	ILCE-7CL 40 FOCUS	ILCE-6700M 40 FOCUS	ILCE-6400Y 40 FOCUS
			ILCE-7M4 40 FOCUS	ILCE-7M3 40 FOCUS				ILCE-6700L 40 FOCUS	ILCE-6400L 40 FOCUS
附属镜头 Kit lens	—	—	FE 28-70mm F3.5-5.6 OSS (SEL2870)	FE 28-70mm, F3.5-5.6 OSS	—	FE 28-60mm F4-5.6 OSS (SEL2860)	FE 28-60mm F4-5.6 OSS (SEL2860)	E 18-135mm F3.5-5.6 OSS E PZ 16-50mm F3.5-5.6 OSS	E PZ 16-50mm, F3.5-5.6 OSS E 55-210mm, F4.5-6.3 OSS E PZ 16-50mm, F3.5-5.6 OSS
影像传感器 Image Sensor	FULL FRAME Exmor RS CMOS Sensor	FULL FRAME Exmor RS CMOS Sensor	FULL FRAME Exmor RS CMOS Sensor	FULL FRAME Exmor RS CMOS Sensor	FULL FRAME Exmor RS CMOS Sensor	FULL FRAME Exmor RS CMOS Sensor	FULL FRAME Exmor RS CMOS Sensor	Exmor RS CMOS Sensor	Exmor RS FPS HD CMOS
像素 Effective no. of pixels	24.2 Megapixels	61.0 Megapixels	33.0 Megapixels	24.2 Megapixels	61.0 Megapixels	33.0 Megapixels	24.2 Megapixels	26.0 Megapixels	24.2 Megapixels
ISO感光度 ISO sensitivity	ISO 100-51200 ^{*1} Expandable up to 204800	ISO 100-32000 ^{*2} Expandable up to 102400	ISO 100-51200 ^{*3} Expandable up to 204800	ISO 100-51200 ^{*3} Expandable up to 204800	ISO 100-32000 ^{*4} Expandable to ISO 50-102400	ISO 100-51200 ^{*3} Expandable to ISO 50-204800	ISO 100-51200 ^{*3} Expandable up to 204800	ISO 100-32000 ^{*4} Expandable to ISO 50-102400	ISO 100-32000 ^{*5} Expandable up to 102400
对焦系统类型 Focus type	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]
对焦点 Focus point	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 693 points (Contrast-detection AF)	759 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	Still images: Max. 693 points (Phase-detection AF), Movies: Max. 693 points (Phase-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 627 points (Phase-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 495 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)
连拍 Continuous shooting	Max. 20 fps	Max. 10 fps	Max. 10 fps	Max. 10 fps	Hi+: 8 fps	Hi+: 10 fps	Max. 10 fps	Hi+: 11 fps	Max. 11 fps
动画的影像尺寸 Movie image size	4K ^{*6} XAVC S 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC S 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC HS 4K : 3,840 x 2,160 (4:2:0, 10bit)	4K HDR ^{*7} XAVC S 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC S 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC S 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC S 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC HS 4K : 3,840 x 2,160	4K HDR ^{*7} XAVC S 4K : 3,840 x 2,160
Wi-Fi/NFC Wi-Fi/NFC	● / ●	● / —	● / —	● / ●	● / —	● / —	● / ●	● / —	● / ●
PAL/NTSC PAL/NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
取景器 Viewfinder	Quad-VGA OLED Tru-Finder	Quad-VGA OLED Tru-Finder	XGA OLED Tru-Finder	XGA OLED Tru-Finder	Quad-VGA OLED Tru-Finder	Quad-VGA OLED Tru-Finder	XGA OLED Tru-Finder	Quad-VGA OLED Tru-Finder	XGA OLED Tru-Finder
液晶显示屏 LCD Monitor	3.0 type (1,440K dots)	3.2 type (2,095K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)
重量 Weight (仅主机/Body only)	约 593 g	约 638 g	约 573 g	约 565 g	约 430 g	约 429 g	约 424 g	约 409 g	约 359 g

*1 拍摄静止影像可扩展到ISO 50-204800。Expandable to ISO 50-204800 for shooting still images. *2 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. *3 拍摄静止影像可扩展到ISO 204800。Expandable to ISO 204800 for shooting still images. *4 拍摄静止影像可扩展到ISO 50-102400。Expandable ISO 50-102400 is available for still images. *5 拍摄静止影像可扩展到ISO 100-102400。Expandable to ISO 100-102400 for shooting still images. *6 3,840 x 2,160 pixels. *7 播放HDR动画时,通过USB连接线将本产品连接到兼容HDR(HLG)的索尼电视上播放。Connect to an HDR (HLG) compatible Sony TV via a USB cable when displaying HDR (HLG) movies. : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection. : 有此标识的商品已停产,库存数量可能有限或已售罄。选购前请先与店方确认。