

镜头兼容性 Lens Compatibility	E-mount lenses								
机型名称 Model Name	α7RⅥ	α7RⅤ	α7Ⅴ	α7Ⅳ	α7Ⅲ	α7CR	α7CⅡ	α6700	α6400
	ILCE-7RM6	ILCE-7RM5	ILCE-7M5M	ILCE-7M4M	ILCE-7M3K	ILCE-7CR	ILCE-7CM2L	ILCE-6700M	ILCE-6400X
			  	  	  	  	  	  	 
	 	 	ILCE-7M5   	ILCE-7M4   	ILCE-7M3   	 	 	ILCE-6700K   	ILCE-6400K  
附属镜头 Kit lens	—	—	FE 28-70mm F3.5-5.6 OSS II (SEL28702)	FE 28-70mm F3.5-5.6 OSS II (SEL28702)	FE 28-70mm F3.5-5.6 OSS	—	FE 28-60mm F4-5.6 OSS (SEL2860)	E 18-135mm F3.5-5.6 OSS	E PZ 16-50mm F3.5-5.6 OSS II E 55-210mm F4.5-6.3 OSS
	—	—	—	—	—	—	—	E PZ 16-50mm F3.5-5.6 OSS II	E PZ 16-50mm F3.5-5.6 OSS II
影像传感器 Image Sensor	 	 	 	 	 	 	 		
像素 Effective no. of pixels	66.8 Megapixels	61.0 Megapixels	33.0 Megapixels	33.0 Megapixels	24.2 Megapixels	61.0 Megapixels	33.0 Megapixels	26.0 Megapixels	24.2 Megapixels
ISO感光度 ISO sensitivity	ISO 100-32000 ^{*1} Expandable up to 102400	ISO 100-32000 ^{*1} Expandable up to 102400	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-51200 ^{*2} Expandable to ISO 50-204800	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-32000 ^{*4} Expandable up to 102400
对焦系统类型 Focus type	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]
对焦点 Focus point	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 759 points (Phase-detection AF)	693 points (Phase-detection AF) / 693 points (Contrast-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 759 points (Phase-detection AF)	759 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	Still images: Max. 693 points (Phase-detection AF), Movies: Max. 693 points (Phase-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 627 points (Phase-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 495 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)
连拍 Continuous shooting	Max. 30 fps	Max. 10 fps	Max. 30 fps	Max. 10 fps	Max. 10 fps	Hi+: 8 fps	Hi+: 10 fps	Hi+: 11 fps	Max. 11 fps
动画的影像尺寸 Movie image size	 ^{*5} XAVC HS 8K : 7680 x 4320	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC HS 4K : 3,840 x 2,160 (4:2:0, 10bit)	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC HS 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160
Wi-Fi/NFC Wi-Fi/NFC	● / —	● / —	● / —	● / —	● / ●	● / —	● / —	● / —	● / ●
PAL/NTSC PAL/NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
取景器 Viewfinder									
液晶显示屏 LCD Monitor	3.2 type (2,095K dots)	3.2 type (2,095K dots)	3.2 type (2,095K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)
重量 Weight (仅主机/Body only)	约 713 g	约 638 g	约 695 g	约 573 g	约 565 g	约 430 g	约 429 g	约 409 g	约 359 g

^{*1} 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. ^{*2} 拍摄静止影像可扩展到ISO 204800。Expandable to ISO 204800 for shooting still images. ^{*3} 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. ^{*4} 拍摄静止影像可扩展到ISO 100-102400。Expandable to ISO 100-102400 for shooting still images.
^{*5} 在进行 8K 录制时，[APS-C S35 拍摄] 模式将固定为 [关闭]。建议使用全画幅 35 毫米镜头。进行 8K 录制时，视角会缩小。 [APS-C S35 shooting] is fixed [Off] during 8K recording. A full-frame 35 mm lens is recommended.Angle of view is reduced for 8K recording. ^{*6} 播放HDR动画时,通过USB连接线将本产品连接到可兼容HDR(HLG)的索尼电视上播放。Connect to an HDR (HLG) compatible Sony TV via a USB cable when displaying HDR (HLG) movies.
 : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection.  : 有此标识的商品已停产，库存数量可能有限或已售罄。选购前请先与店方确认。

Contents are valid as of August 2026.


VLOG相机 | Digital Camera VLOGCAM™

Cyber-shot 数码相机 | Digital Still Camera

机型名称 Model Name		VLOGCAM ZV-E1L	VLOGCAM ZV-E10M2K	VLOGCAM ZV-E10K	VLOGCAM ZV-1M2	VLOGCAM ZV-1F
						
影像传感器 Image sensor	传感器类型 Type					
	像素数 (約) Effective pixels (approx.)	12.1M	26.0M	24.2M	20.1M	20.1M
镜头 Lens	镜头兼容性 Focal Length*1 35mm format equivalent 附属镜头 Kit Lens	E-mount lens SEL2860 FE 28-60 mm F4-5.6 (167g)	E-mount lens E PZ 16-50mm F3.5-5.6 OSS II (107g)	E-mount lens E PZ 16-50mm F3.5-5.6 OSS II (107g)	18-50mm F1.8-4.0 (35mm equiv.) ZEISS®	20 mm (7.6mm) ZEISS®
ISO感光度设定 ISO	感光度设定 Still	ISO 80 – 102400 (expanded ISO 40 – 409600)	ISO 100 – 32000 (expandable to ISO 50 - 102400)	ISO 100 – 32000 (expanded ISO 50 – 51200)	ISO 125 – 12800 (expandable to ISO 80 – 12800)	ISO 125 – 12800 (expanded ISO 80 – 12800)
	动态影像 Movie	ISO 80 – 102400 (expanded ISO 40 – 409600)	ISO 100 – 32000	ISO 100 – 32000	ISO 125 – 12800 equivalent	ISO 125 – 12800
自动对焦 AF	类型 Focus type	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Contrast AF
	对焦点 Focus point	Still images: Max. 759 points (phase-detection AF), Movies: Max. 627 points (phase-detection AF)	Still images: Max. 759 points (phase-detection AF), Movies: Max. 495 points (phase-detection AF)	425 (phase-detection) / 425 (contrast-detection)	Still images: Max. 315 points (phase-detection AF), Movies: Max. 273 points (phase-detection AF)	425 (contrast-detection)
液晶屏 LCD screen	液晶屏尺寸/液晶屏总像素 Type / number of dots	3.0-type / 1036k dots	3.0-type / 1036k dots	3.0-type / 921 k dots	3.0-type / 921.6k dots	3.0-type / 921 k dots
	Type / Touch panel	Vari-angle / ●	Vari-angle / ●	Vari-angle / ●	Vari-angle / ●	Vari-angle / ●
驱动器 Drive	Continuous Drive Speed (max)	Hi+: 10fps	Hi+: 11 fps	Hi+: 11 fps	24fps	16fps
视频 Movie	4K	●	●	●	●	●
	混合对数-伽马 HLG Hybrid Log-Gamma	●	●	●	●	●
	慢动作和快动作 S&Q Slow & Quick Motion	●	●	●	●	●
连接性 Connectivity	Wi-Fi / NFC / Bluetooth	Yes (2.4GHz / 5 GHz) / — / Yes	Yes (2.4GHz / 5 GHz) / — / Yes	Yes (2.4GHz) / — / Yes	Yes (2.4GHz) / — / Yes	Yes (2.4GHz) / — / Yes
多功能热靴接口 / 麦克风插孔 Accessory shoe / Microphone jack		● / ●	● / ●	● / ●	● / ●	● (No electronic contacts) / ●
电源 Power	电池 Battery	NP-FZ100	NP-FZ100	NP-FW50	NP-BX1	NP-BX1
	电池使用时间 Battery life (CIPA standard)	Approx. 570 shots (LCD)*2 Approx. 95 min (LCD, actual recording)*2	Approx. 610 shots (LCD)*2 Approx. 130 min (LCD, actual recording)*2	Approx. 440 shots (LCD)*2 Approx. 80 min (LCD, actual recording)*2	Approx. 290 shots (LCD)*2 Approx. 45 min (LCD, actual recording)*2	Approx. 360 (LCD)*2 Approx. 60 min (LCD, actual recording)*2
重量 Weight (仅主机/Body only) (g)		Approx. 399g	Approx. 292g	Approx. 299g	Approx. 266g	Approx. 229g

机型名称 Model Name		DSC-RX10M5
		
影像传感器 Image sensor	传感器类型 Type	1.0-type 
	像素数 (約) Effective pixels (approx.)	20.1M
镜头 Lens	镜头兼容性 Focal Length*1 35mm format equivalent	24-600mm F2.4-4.0 (35mm equiv.) ZEISS®
ISO感光度设定 ISO	感光度设定 Still	ISO 100 – 12800 (expandable to ISO 64)
	动态影像 Movie	ISO 100 – 12800 equivalent
自动对焦 AF	类型 Focus type	Fast Hybrid AF (phase-detection AF / contrast-detection AF)
	对焦点 Focus point	Still images: Max. 575 points (phase-detection AF), Movies: Max. 575 points (phase-detection AF)
液晶屏 LCD screen	液晶屏尺寸/液晶屏总像素 Type / number of dots	3.0-type / 1620k dots
	Type / Touch panel	Tilt-type / ●
驱动器 Drive	Continuous Drive Speed (max)	Hi+: 30 fps
视频 Movie	4K	●
	混合对数-伽马 HLG Hybrid Log-Gamma	●
	慢动作和快动作 S&Q Slow & Quick Motion	●
连接性 Connectivity	Wi-Fi / NFC / Bluetooth	Yes (2.4GHz / 5 GHz) / — / Yes
多功能热靴接口 / 麦克风插孔 Accessory shoe / Microphone jack		● / ●
电源 Power	电池 Battery	NP-FZ100
	电池使用时间 Battery life (CIPA standard)	Approx. 630 shots (LCD)*2 Approx. 120 min (LCD, actual recording)*2
重量 Weight (仅主机/Body only) (g)		Approx. 1026g

*1 最大像素读出量 Maximum pixel readout *2 当使用液晶显示器时 For LCD monitor use
■ : 有此标识的商品已停产，库存数量可能有限或已售罄。选购前请先与店方确认。 ■ : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection.

	无线头戴式耳机 Wireless Over Head Band Headphones						真无线耳机 Truly Wireless Headphones					
机型 Model	1000X THE Collexion	WH-1000X M6	WH-1000X M5	WH-ULT900N	WH-CH720N	WH-CH520	WF-1000X M6	WF-1000X M5	LinkBuds Fit	LinkBuds Clip	WF-C710N	WF-C510
												
降噪 Noise Canceling	★★★★★	★★★★★	★★★★★	★★★★	★★★	—	★★★★★	★★★★★	★★★★★	—	★★★★★	—
高解析度音频 Hi-Resolution				—	—	—				—	—	—
高音质 High Sound Quality												
重低音 Deep Bass	—	—	—	ULT sound modes	—	—	—	—	—	—	—	—
使用时间 Continuous Playback Time	约24小时 Approx.24h (降噪打开) (Noise Canceling ON)	约30小时 Approx.30h (降噪打开) (Noise Canceling ON)	约30小时 Approx.30h (降噪打开) (Noise Canceling ON)	约30小时 Approx.30h (降噪打开) (Noise Canceling ON)	约35小时 Approx.35h (降噪打开) (Noise Canceling ON)	约50小时 Approx.50h	耳机：约8小时 充电盒：约16小时 Headset：Approx.8h Charging Case：Approx.16h (降噪打开) (Noise Canceling ON)	耳机：约8小时 充电盒：约16小时 Headset：Approx.8h Charging Case：Approx.16h (降噪打开) (Noise Canceling ON)	耳机：约5.5小时 充电盒：约15.5小时 Headset：Approx.5.5h Charging Case：Approx.15.5h	耳机：约9小时 充电盒：约28小时 Headset：Approx.9h Charging Case：Approx.28h	耳机：约8.5小时 充电盒：约21.5小时 Headset：Approx.8.5h Charging Case：Approx.21.5h (降噪打开) (Noise Canceling ON)	耳机：约11小时 充电盒：约11小时 Headset：Approx.11h Charging Case：Approx.11h
充电时间 Charging Time	约3.5小时 Approx.3.5h	约3.5小时 Approx.3.5h	约3.5小时 Approx.3.5h	约3.5小时 Approx.3.5h	约3.5小时 Approx.3.5h	约3小时 Approx.3h	耳机：约1.5小时 充电盒：约2小时 Headset：Approx.1.5h Charging Case：Approx.2h	耳机：约1.5小时 充电盒：约2小时 Headset：Approx.1.5h Charging Case：Approx.2h	耳机：约2小时 充电盒：约3小时 Headset：Approx.2h Charging Case：Approx.3h	耳机：约1.5小时 充电盒：约3小时 Headset：Approx.1.5h Charging Case：Approx.3h	耳机：约1.5小时 充电盒：约3.5小时 Headset：Approx.1.5h Charging Case：Approx.3.5h	耳机：约1.5小时 充电盒：约3小时 Headset：Approx.1.5h Charging Case：Approx.3h
防水等级 Waterproof	—	—	—	—	—	—	IPX4级防泼溅 IPX4 Splash-proof	IPX4级防泼溅 IPX4 Splash-proof	IPX4级防泼溅 IPX4 Splash-proof	IPX4级防泼溅 IPX4 Splash-proof	IPX4级防泼溅 IPX4 Splash-proof	IPX4级防泼溅 IPX4 Splash-proof
支持的编解码器 Bluetooth Cordec	SBC/AAC/LDAC/LC3	SBC/AAC/LDAC/LC3	SBC/AAC/LDAC	SBC/AAC/LDAC	SBC/AAC	SBC/AAC	SBC/AAC/LDAC/LC3	SBC/AAC/LDAC/LC3	SBC/AAC/LDAC/LC3	SBC/AAC	SBC/AAC	SBC/AAC
重量 Weights	约320g Approx.320g	约254g Approx.254g	约250g Approx.250g	约255g Approx.255g	约192g Approx.192g	约147g Approx.147g	耳机：约6.5g×2 充电盒：约45g Headset：Approx.6.5g×2 Charging Case：Approx.45g	耳机：约5.9g×2 充电盒：约39g Headset：Approx.5.9g×2 Charging Case：Approx.39g	耳机：约4.9g×2 充电盒：约41g Headset：Approx.4.9g×2 Charging Case：Approx.41g	耳机：约6.4g×2 充电盒：约42g Headset：Approx.6.4g×2 Charging Case：Approx.42g	耳机：约5.2g×2 充电盒：约38g Headset：Approx.5.2g×2 Charging Case：Approx.38g	耳机：约4.6g×2 充电盒：约31g Headset：Approx.4.6g×2 Charging Case：Approx.31g
包装清单 Supplied Accessories	•耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携袋 Carrying pouch	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携袋 Carrying pouch	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携袋 Carrying pouch	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携袋 Carrying pouch	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携袋 Carrying pouch	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm)	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳塞 (SS/SS/M/L每种尺寸2个) Noise Isolation Earbud Tips (XS/S/M/L 2 each) •充电盒 Charging case	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳塞 (SS/S/M/L每种尺寸2个) Noise Isolation Earbud Tips (SS/S/M/L 2 each) •充电盒 Charging case	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳塞 (SS/S/M/L每种尺寸2个) Noise Isolation Earbud Tips (SS/S/M/L 2 each) •充电盒 Charging case	•衬垫 Fitting Cushions •充电盒 Charging case	•USB Type-C®连接线 (USB-A至USB-C®) (约20 cm) USB Type-C® cable (USB-A to USB-C®) (approx. 20 cm) •耳塞 (SS/M/XL每种尺寸2个) Noise Isolation Earbud Tips (XS/M/XL 2 each) •充电盒 Charging case	•混合硅胶耳塞 (SS/M/LL每种尺寸2个) Hybrid silicone rubber earbuds (SS/M/LL 2 each) •充电盒 Charging case

MP3播放器 | Walkman®

Model Name 机型名称	NW-WS623	NW-E394 
		
Capacity 容量	4GB	8GB
Colors 颜色	Black / Grayish White  / Blue / Lime Green 	Black / Blue / Red
Usage 用途	Music	Music / Photo / FM
FM Tuner FM调频	—	● (87.5 to 108.0 MHz)
φ4.4mm Balanced Connection φ4.4mm平衡连接	—	—
Audio Formats(Codec) 音频格式(编解码器)	MP3 / WMA / AAC / Linear PCM / FLAC ^{*2}	MP3 / WMA / AAC / Linear PCM
Photo Format(Codec) 照片格式(编解码器)	—	JPEG
Display 显示	—	1.77 inch, TFT color display
Dimensions(W×H×D)(Approx.) 尺寸(宽×高×深)(约)	—	43.2×92.3×9.6mm
Mass(Approx.) 重量(约)	32g	39g
Playback Time(Approx.) 播放时间(约)	Music: 12 hours ^{*4 *5}	Music: 35 hours ^{*4}
USB-based Charging Time(Approx.) USB充电时间(约)	1.5 hours (Built-in Lithium-ion Battery)	2 hours (Built-in Lithium-ion Battery)
System Requirements Computer 系统要求电脑	Windows / Mac	Windows / Mac
3minutes Charge 3分钟充电	Up to 60minutes play back (MP3 128kbps)	—
Menu Display Language 多语言菜单显示	—	English / German / Spanish / French / Italian / Polish / Portuguese / Russian / Turkish / Japanese / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文(繁体中文 / 简体中文)
Instruction Manual Language 使用说明书	English / Arabic / Chinese (Traditional Chinese / Simplified Chinese) 中文(繁体中文 / 简体中文)	English / Arabic / Chinese (Traditional Chinese / Simplified Chinese) 中文(繁体中文 / 简体中文)

^{*1} Copyright protected files cannot be played back. Sampling frequency may not correspond to all encoders. Files that are 4 GB (APE is 2GB) or larger cannot be played back. (不会播放受著作权保护的文件。有关支持的音频文件的比特率和采样频率等信息,请参考产品说明书。大于4GB的文件(APE仅2GB)无法播放。) ^{*2} For sampling frequency over 352.8 kHz, it will be down convert playback. (它将在352.8kHz以上进行下转换播放) ^{*3} Some photo files cannot be played back, depending on their file formats. (根据文件格式的不同,某些照片文件无法重放。) ^{*4} When playing MP3 128kbps. (当播放MP3 128kbps时。) ^{*5} Ambient sound function: OFF. (环境声模式:关闭。)

 : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection.

 比标识的商品已停产,库存数量可能有限或已售罄。选购前请先与店方确认。

便携式蓝牙音箱 | Wireless Portable Speaker

Model 机型	SRS-ULT10	SRS-XB100
		
Speaker System 扬声器系统	Woofer/Tweeter Passive Radiator	Full range Passive radiator
Speaker Add Function 扬声器添加功能	● (Stereo Pair)	● (Stereo/Double)
Bluetooth® enabled product 蓝牙™ enabled product	●	●
ULT ^{POWER SOUND}	●	—
Hands-Free Function 免提	●	●
Water-proof / Dust-proof 防水 / 防尘	● ^{*1 *2} With IP67 waterproof and dustproof IP67防尘防水	● ^{*1 *2}
Strap belt 背带	● Adjustable lanyard length Detachable 挂绳长度可调 可拆卸	●
Battery Life (Approx.) 电池寿命(约)	12h Battery Charging Time : 5.0h	16h Battery Charging Time : 4.5h
USB Charge USB充电	●	●
Dimensions(W×H×D):mm (Approx.) 尺寸(宽×高×深)(约)	206×77×76	Φ76×95
Weights (Approx.) 重量(约)	650g	274g
Instruction Manual Language 使用说明书	English/Chinese(Traditional) 中文/ Korean/Thai/Indonesian/Arabic	English/Chinese(Traditional) 中文/ Korean/Thai/Indonesian/Arabic

^{*1} IPX7 equivalency: The speaker has been tested to and maintains its operability when gently submersed in water to a depth of 1 m and left for 30 minutes. IPX7 (持续浸水防护等级): 经过测试,当浸于约1米深的水中约30分钟时,仍然可以保持其操作性。 ^{*2} IP6X equivalency: The speaker has been tested to and continues to block dust after stirring for 8 hours in a testing device which contains dust particles that are up to 75 μm in diameter IP6X (灰尘防护等级) 经过测试,在含有最大直径约75微米的灰尘颗粒的测试设备中晃动约8小时后,仍然可以持续防尘。

 : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection.

 : 有此标识的商品已停产,库存数量可能有限或已售罄。选购前请先与店方确认。