

镜头兼容性 Lens Compatibility	E-mount lenses								
机型名称 Model Name	α9II	α9	α7RV	α7RIII	α7IV	α7III	α7C	α6600	α6400
	ILCE-9M2	ILCE-9	ILCE-7RM5	ILCE-7RM3A	ILCE-7M4K 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-7M3K 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-7CL 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-6600M 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-6400Y 4D FOCUS
	 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-7M4 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-7M3 4D FOCUS 5-axis SteadyShot INSIDE	 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-6600 4D FOCUS 5-axis SteadyShot INSIDE	ILCE-6400L 4D FOCUS			
附属镜头 Kit lens	—	—	—	—	FE 28-70mm F3.5-5.6 OSS (SEL2870)	FE 28-70mm, F3.5-5.6 OSS	FE 28-60mm F4-5.6 OSS (SEL2860)	E 18-135mm, F3.5-5.6 OSS	E PZ 16-50mm, F3.5-5.6 OSS E 55-210mm, F4.5-6.3 OSS E PZ 16-50mm, F3.5-5.6 OSS
影像传感器 Image Sensor									
像素数(约) Effective no. of pixels	24.2 Megapixels	24.2 Megapixels	61.0 Megapixels	42.4 Megapixels	33.0 Megapixels	24.2 Megapixels	24.2 Megapixels	24.2 Megapixels	24.2 Megapixels
ISO感光度 ISO sensitivity	ISO 100-51200*1 Expandable up to 204800	ISO 100-51200*1 Expandable up to 204800	ISO 100-32000*2 Expandable up to 102400	ISO 100-32000*2 Expandable up to 102400	ISO 100-51200*3 Expandable up to 204800	ISO 100-51200*3 Expandable up to 204800	ISO 100-51200*3 Expandable up to 204800	ISO 100-32000*2 Expandable up to 102400	ISO 100-32000*4 Expandable up to 102400
对焦系统类型 Focus type	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]								
对焦点 Focus point	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 693 points (Contrast-detection AF)	399 points (Phase-detection AF) / 425 points (Contrast-detection AF)	759 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)
连拍 Continuous shooting	Max. 20 fps	Max. 20 fps	Max. 10 fps	Max. 11 fps	Max. 11 fps				
动画的影像尺寸 Movie image size	XAVC S 4K : 3,840 x 2,160	XAVC HS 4K : 3,840 x 2,160 (4:2:0, 10bit)	XAVC S 4K : 3,840 x 2,160						
Wi-Fi/NFC Wi-Fi/NFC	● / ●	● / ●	● / —	● / ●	● / —	● / ●	● / ●	● / ●	● / ●
PAL/NTSC PAL/NTSC	PAL / NTSC								
取景器 Viewfinder									
液晶显示屏 LCD Monitor	3.0 type (1,440K dots)	3.0 type (1,440K dots)	3.2 type (2,095K dots)	3.0 type (1,440K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (921K dots)	3.0 type (921K dots)	3.0 type (921K dots)
重量 (仅主机/Body only)	约 593 g	约 588 g	约 638 g	约 572 g	约 573 g	约 565 g	约 424 g	约 418 g	约 359 g

*1 拍摄静止影像可扩展到ISO 50-204800。Expandable to ISO 50-204800 for shooting still images. *2 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. *3 拍摄静止影像可扩展到ISO 204800。Expandable to ISO 204800 for shooting still images. *4 拍摄静止影像可扩展到ISO 100-102400。Expandable to ISO 100-102400 for shooting still images. *5 拍摄静止影像可扩展到ISO 100-51200。Expandable to ISO 100-51200 for shooting still images.
 *6 3,840 x 2,160像素。3,840x2,160 pixels. *7 播放HDR动画时,通过USB连接将本产品连接到兼容HDR(HLG)的索尼电视上播放。Connect to an HDR (HLG) compatible Sony TV via a USB cable when displaying HDR (HLG) movies.
 : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection. : 有此标识的商品已停产,库存数量可能有限或已售罄。订购前请先与店方确认。
 Contents are valid as of February 2023.