







机型名称 Model Name		VLOGCAM ZV-E1L	VLOGCAM ZV-E10L	VLOGCAM ZV-1 II	VLOGCAM ZV-1F/ZV-1FG
 		 			
影像传感器 Image sensor	传感器类型 Type	FULL FRAME Exmor R™ CMOS Sensor	APS-C Exmor CMOS Sensor	1.0-type Exmor R™ CMOS Sensor	1.0-type Exmor R™ CMOS Sensor
	像素数(约) Effective pixels (approx.)	12.1M	24.2M	20.1M	20.1M
镜头 Lens	镜头兼容性 Focal Length*1 35mm format equivalent 附属镜头 Kit Lens	E-mount lens SEL2860 FE 28–60 mm F4–5.6 (167g)	E-mount lens E PZ 16-50mm F3.5-5.6 OSS (SELP1650)	18-50mm F1.8-4.0 (35mm equiv.) ZEISS®	20 mm (7.6mm)
ISO感光度设定 ISO	感光度设定 Still	ISO 80 – 102400 (expanded ISO 40 – 409600)	ISO 100 – 32000 (expanded ISO 50 – 51200)	ISO 125 – 12800 (expandable to ISO 80 – 12800)	ISO 125 – 12800 (expanded ISO 80 – 12800)
	动态影像 Movie	ISO 80 – 102400 (expanded ISO 40 – 409600)	ISO 100 – 32000	ISO 125 – 12800 equivalent	ISO 125 – 12800
自动对焦 AF	类型 Focus type	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Fast Hybrid AF	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Contrast AF
	对焦点 Focus point	Still images: Max. 759 points (phase-detection AF), Movies: Max. 627 points (phase-detection AF)	425 (phase-detection) / 425 (contrast-detection)	Still images: Max. 315 points (phase-detection AF), Movies: Max. 273 points (phase-detection AF)	425 (contrast-detection)
液晶屏 LCD screen	液晶屏尺寸/液晶屏总像素 Type / number of dots	3.0 -type / 1036k dots	3.0 -type / 921k dots	3.0 -type / 921.6k dots	3.0 -type / 921k dots
	Type / Touch panel	Vari-angle / ●	Vari-angle / ●	Vari-angle / ●	Vari-angle / ●
驱动器 Drive	Continuous Drive Speed (max)	Hi+: 10 fps	11 fps (AF / AE tracking)	Hi: 24 fps	16 fps
视频 Movie	4K	●	●	●	●
	Log	● (S-Gamut3.Cine/S-Log3 and S-Gamut3/S-Log3 color science)	● (S-Log2, S-Log3)	● (S-Gamut3.Cine/S-Log3 and S-Gamut3/S-Log3 color science)	● (S-Log2, S-Log3)
	混合对数-伽马 HLG Hybrid Log-Gamma	●	●	●	●
	慢动作和快动作 S&Q Slow & Quick Motion	●	Slow motion 5x (FHD) Quick motion 60x (FHD)	●	Slow motion 5x (FHD) Quick motion 60x (FHD)
连接性 Connectivity	Wi-Fi / NFC / Bluetooth	Yes (2.4GHz / 5 GHz) / — / Yes	Yes (2.4GHz) / — / Yes	Yes (2.4GHz) / — / Yes	Yes (2.4GHz) / — / Yes
多功能热靴接口 / 麦克风插孔 Accessory shoe / Microphone jack		● / ●	● / ●	● / ●	● (No electronic contacts) / ●
电源 Power	电池 Battery	NP-FZ100	NP-FW50	NP-BX1	NP-BX1
	电池使用时间 Battery life (CIPA standard)	Approx. 570 shots (LCD)*2 Approx. 95 min (LCD, actual recording)*2	Approx. 440 shots (LCD)*2 Approx. 80 min (LCD, actual recording)*2	Approx. 290 shots (LCD)*2 Approx. 45 min (LCD, actual recording)*2	Approx. 360 (LCD)*2 Approx. 60 min (LCD, actual recording)*2
重量 Weight (仅主机/Body only) (g)		399g	299g	Approx. 292g	229g

*1 最大像素读出量 Maximum pixel readout *2 当使用液晶显示器时 For LCD monitor use