

镜头兼容性 Lens Compatibility	E-mount lenses									
	α7R V	α7 V	α7 IV	α7 III	α7CR	α7C II	α6700		α6400	
机型名称 Model Name	ILCE-7RM5 	ILCE-7M5 	ILCE-7M4K 	ILCE-7M3K 	ILCE-7CR 	ILCE-7CM2L 	ILCE-6700M 	ILCE-6700K 	ILCE-6400X 	ILCE-6400K
附属镜头 Kit lens	—	—	FE 28-70mm F3.5-5.6 OSS (SEL2870)	FE 28-70mm F3.5-5.6 OSS	—	FE 28-60mm F4-5.6 OSS (SEL2860)	E 18-135mm F3.5-5.6 OSS	E PZ 16-50mm F3.5-5.6 OSS II E PZ 16-50mm F3.5-5.6 OSS	E PZ 16-50mm F3.5-5.6 OSS II E 55-210mm F4.5-6.3 OSS E PZ 16-50mm F3.5-5.6 OSS E 55-210mm F4.5-6.3 OSS	E PZ 16-50mm F3.5-5.6 OSS II
影像传感器 Image Sensor										
像素 Effective no. of pixels	61.0 Megapixels	33.0 Megapixels	33.0 Megapixels	24.2 Megapixels	61.0 Megapixels	33.0 Megapixels	26.0 Megapixels	26.0 Megapixels	24.2 Megapixels	24.2 Megapixels
ISO感光度 ISO sensitivity	ISO 100-32000 ^{*1} Expandable up to 102400	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-51200 ^{*2} Expandable to ISO 50-204800	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-32000 ^{*4} Expandable up to 102400	ISO 100-32000 ^{*4} Expandable up to 102400
对焦系统类型 Focus type	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]
对焦点 Focus point	693 points (Phase-detection AF) / 693 points (Contrast-detection AF)	Still Images: Max. 759 points (Phase-detection AF), Movies: Max. 759 points (Phase-detection AF)	759 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	Still Images: Max. 693 points (Phase-detection AF), Movies: Max. 693 points (Phase-detection AF)	Still Images: Max. 759 points (Phase-detection AF), Movies: Max. 627 points (Phase-detection AF)	Still Images: Max. 759 points (Phase-detection AF), Movies: Max. 495 points (Contrast-detection AF)	Still Images: Max. 759 points (Phase-detection AF), Movies: Max. 495 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)
连拍 Continuous shooting	Max. 10 fps	Max. 30 fps	Max. 10 fps	Max. 10 fps	Hi+: 8 fps	Hi+: 10 fps	Hi+: 11 fps	Hi+: 11 fps	Max. 11 fps	Max. 11 fps
动画的影像尺寸 Movie image size	XAVC S 4K : 3,840 x 2,160	XAVC S 4K : 3,840 x 2,160	XAVC HS 4K : 3,840 x 2,160 (4:2:0, 10bit)	XAVC S 4K : 3,840 x 2,160	XAVC S 4K : 3,840 x 2,160	XAVC S 4K : 3,840 x 2,160	XAVC HS 4K : 3,840 x 2,160	XAVC HS 4K : 3,840 x 2,160	XAVC S 4K : 3,840 x 2,160	XAVC S 4K : 3,840 x 2,160
Wi-Fi/NFC Wi-Fi/NFC	● / —	● / —	● / —	● / ●	● / —	● / —	● / —	● / —	● / ●	● / ●
PAL/NTSC PAL/NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
取景器 Viewfinder										
液晶显示屏 LCD Monitor	3.2 type (2,095K dots)	3.2 type (2,095K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (921K dots)
重量 Weight (仅主机/Body only)	约 638 g	约 695 g	约 573 g	约 565 g	约 430 g	约 429 g	约 409 g	约 409 g	约 359 g	约 359 g

*1 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. *2 拍摄静止影像可扩展到ISO 204800。Expandable to ISO 204800 for shooting still images. *3 拍摄静止影像可扩展到ISO 50-102400。Expandable ISO 50-102400 is available for still images. *4 拍摄静止影像可扩展到ISO 100-102400。Expandable to ISO 100-102400 for shooting still images.

*5 播放HDR动画时,通过USB连接线将本产品连接到可兼容HDR(HLG)的索尼电视上播放。Connect to an HDR (HLG) compatible Sony TV via a USB cable when displaying HDR (HLG) movies.

: Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection. : 有此标识的商品已停产,库存数量可能有限或已售罄。选购前请先与店方确认。