

镜头兼容性 Lens Compatibility	E-mount lenses								
机型名称 Model Name	α7RⅥ	α7RⅤ	α7Ⅴ	α7Ⅳ	α7Ⅲ	α7CR	α7CⅡ	α6700	α6400
	ILCE-7RM6	ILCE-7RM5	ILCE-7M5M	ILCE-7M4M	ILCE-7M3K	ILCE-7CR	ILCE-7CM2L	ILCE-6700M	ILCE-6400X
									
	 	 	 	 	 	 	 	 	
附属镜头 Kit lens	—	—	FE 28-70mm F3.5-5.6 OSS II (SEL28702)	FE 28-70mm F3.5-5.6 OSS II (SEL28702)	FE 28-70mm F3.5-5.6 OSS	—	FE 28-60mm F4-5.6 OSS (SEL2860)	E 18-135mm F3.5-5.6 OSS	E PZ 16-50mm F3.5-5.6 OSS II E 55-210mm F4.5-6.3 OSS
	—	—	—	—	—	—	—	E PZ 16-50mm F3.5-5.6 OSS II	E PZ 16-50mm F3.5-5.6 OSS II
影像传感器 Image Sensor									
像素 Effective no. of pixels	66.8 Megapixels	61.0 Megapixels	33.0 Megapixels	33.0 Megapixels	24.2 Megapixels	61.0 Megapixels	33.0 Megapixels	26.0 Megapixels	24.2 Megapixels
ISO感光度 ISO sensitivity	ISO 100-32000 ^{*1} Expandable up to 102400	ISO 100-32000 ^{*1} Expandable up to 102400	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-51200 ^{*2} Expandable up to 204800	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-51200 ^{*2} Expandable to ISO 50-204800	ISO 100-32000 ^{*3} Expandable to ISO 50-102400	ISO 100-32000 ^{*4} Expandable up to 102400
对焦系统类型 Focus type	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]
对焦点 Focus point	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 759 points (Phase-detection AF)	693 points (Phase-detection AF) / 693 points (Contrast-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 759 points (Phase-detection AF)	759 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	Still images: Max. 693 points (Phase-detection AF), Movies: Max. 693 points (Phase-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 627 points (Phase-detection AF)	Still images: Max. 759 points (Phase-detection AF), Movies: Max. 495 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)
连拍 Continuous shooting	Max. 30 fps	Max. 10 fps	Max. 30 fps	Max. 10 fps	Max. 10 fps	Hi+: 8 fps	Hi+: 10 fps	Hi+: 11 fps	Max. 11 fps
动画的影像尺寸 Movie image size	 ^{*5} XAVC HS 8K : 7680 x 4320	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC HS 4K : 3,840 x 2,160 (4:2:0, 10bit)	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC HS 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160
Wi-Fi/NFC Wi-Fi/NFC	● / —	● / —	● / —	● / —	● / ●	● / —	● / —	● / —	● / ●
PAL/NTSC PAL/NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
取景器 Viewfinder									
液晶显示屏 LCD Monitor	3.2 type (2,095K dots)	3.2 type (2,095K dots)	3.2 type (2,095K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (1,036K dots)	3.0 type (921K dots)
重量 Weight (仅主机/Body only)	约 713 g	约 638 g	约 695 g	约 573 g	约 565 g	约 430 g	约 429 g	约 409 g	约 359 g

^{*1} 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. ^{*2} 拍摄静止影像可扩展到ISO 204800。Expandable to ISO 204800 for shooting still images. ^{*3} 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. ^{*4} 拍摄静止影像可扩展到ISO 100-102400。Expandable to ISO 100-102400 for shooting still images.
^{*5} 在进行 8K 录制时，[APS-C S35 拍摄] 模式将固定为 [关闭]。建议使用全画幅 35 毫米镜头。进行 8K 录制时，视角会缩小。 [APS-C S35 shooting] is fixed [Off] during 8K recording. A full-frame 35 mm lens is recommended.Angle of view is reduced for 8K recording. ^{*6} 播放HDR动画时,通过USB连接线将本产品连接到可兼容HDR(HLG)的索尼电视上播放。Connect to an HDR (HLG) compatible Sony TV via a USB cable when displaying HDR (HLG) movies.
 : Products with this mark have been discontinued, and thus may be in short supply or out of stock. Please confirm availability with the store before making a selection.  : 有此标识的商品已停产, 库存数量可能有限或已售罄。连购前请先与店方确认。

Contents are valid as of August 2026.