





镜头兼容性 Lens Compatibility	E-mount lenses											
机型名称 Model Name	α 9 II	α 9	α 7 R IV	α 7 R III	α 7 R II	α 7 III	α 7 II	α 6600	α 6400	α 6100	α 6000	α 5100
	ILCE-9M2	ILCE-9KIT	ILCE-7RM4	ILCE-7RM3KIT	ILCE-7RM2KIT	ILCE-7M3K	ILCE-7M2K	ILCE-6600M	ILCE-6400Y	ILCE-6100Y	ILCE-6000Y	ILCE-5100L
	  	    ILCE-9   	  	    ILCE-7RM3   	    ILCE-7RM2  	    ILCE-7M3   	  ILCE-7M2  	   ILCE-6600   	  ILCE-6400L  	  ILCE-6100L  	  ILCE-6000L  	 
	—	Vario-Tessar T* FE 24-70mm, F4 ZA OSS	—	Vario-Tessar T* FE 24-70mm, F4 ZA OSS	Vario-Tessar T* FE 24-70mm, F4 ZA OSS	FE 28-70mm, F3.5-5.6 OSS	FE 28-70mm, F3.5-5.6 OSS	E 18-135mm, F3.5-5.6 OSS	E PZ 16-50mm, F3.5-5.6 OSS E 55-210mm, F4.5-6.3 OSS	E PZ 16-50mm, F3.5-5.6 OSS E 55-210mm, F4.5-6.3 OSS	E PZ 16-50mm, F3.5-5.6 OSS E 55-210mm, F4.5-6.3 OSS	E PZ 16-50mm, F3.5-5.6 OSS
	—	—	—	—	—	—	—	—	E PZ 16-50mm, F3.5-5.6 OSS	E PZ 16-50mm, F3.5-5.6 OSS	E PZ 16-50mm, F3.5-5.6 OSS	E PZ 16-50mm, F3.5-5.6 OSS
影像传感器 Image Sensor	 FULL FRAME <i>Exmor RS</i> CMOS Sensor	 FULL FRAME <i>Exmor RS</i> CMOS Sensor	 FULL FRAME <i>Exmor R</i> CMOS Sensor	 FULL FRAME <i>Exmor R</i> CMOS Sensor	 FULL FRAME <i>Exmor R</i> CMOS Sensor	 FULL FRAME <i>Exmor R</i> CMOS Sensor	 FULL FRAME <i>Exmor R</i> CMOS Sensor	 FULL FRAME <i>Exmor</i> APS HD CMOS	 <i>Exmor</i> APS HD CMOS	 <i>Exmor</i> APS HD CMOS	 <i>Exmor</i> APS HD CMOS	 <i>Exmor</i> APS HD CMOS
像素数(约) Effective no. of pixels	24.2 Megapixels	24.2 Megapixels	61.0 Megapixels	42.4 Megapixels	42.4 Megapixels	24.2 Megapixels	24.3 Megapixels	24.2 Megapixels	24.2 Megapixels	24.2 Megapixels	24.3 Megapixels	24.3 Megapixels
ISO感光度 ISO sensitivity	ISO 100-51200 ^{*1} Expandable up to 204800	ISO 100-51200 ^{*1} Expandable up to 204800	ISO 100-32000 ^{*2} Expandable up to 102400	ISO 100-32000 ^{*2} Expandable up to 102400	ISO 100-25600 ^{*2} Expandable up to 102400	ISO 100-51200 ^{*3} Expandable up to 204800	ISO 100-25600	ISO 100-32000 ^{*2} Expandable up to 102400	ISO 100-32000 ^{*4} Expandable up to 102400	ISO 100-32000 ^{*5} Expandable up to 51200	ISO 100-25600	ISO 100-25600
对焦系统类型 Focus type	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]	Fast Hybrid AF [Phase-detection AF / Contrast-detection AF]
对焦点 Focus point	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	567 points (Phase-detection AF) / 425 points (Contrast-detection AF)	399 points (Phase-detection AF) / 425 points (Contrast-detection AF)	399 points (Phase-detection AF) / 25 points (Contrast-detection AF)	693 points (Phase-detection AF) / 425 points (Contrast-detection AF)	117 points (Phase-detection AF) / 25 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)	425 points (Phase-detection AF) / 425 points (Contrast-detection AF)	179 points (Phase-detection AF) / 25 points (Contrast-detection AF)	179 points (Phase-detection AF) / 25 points (Contrast-detection AF)
连拍 Continuous shooting	Max. 20 fps	Max. 20 fps	Max. 10 fps	Max. 10 fps	Max. 5 fps	Max. 10 fps	Max. 5 fps	Max. 11 fps	Max. 11 fps	Max. 11 fps	Max. 11 fps	Max. 6 fps
动画的影像尺寸 Movie image size	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*7} XAVC S 4K : 3,840 x 2,160	 ^{*7} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 ^{*7} XAVC S 4K : 3,840 x 2,160	 XAVC S / AVCHD : 1,920 x 1,080	 ^{*7} XAVC S 4K : 3,840 x 2,160	 ^{*7} XAVC S 4K : 3,840 x 2,160	 ^{*6} XAVC S 4K : 3,840 x 2,160	 AVCHD : 1,920 x 1,080	 XAVC S / AVCHD : 1,920 x 1,080
Wi-Fi/NFC/QR码 Wi-Fi/NFC/QR code	● / ● / ●	● / ● / ●	● / ● / ●	● / ● / ●	● / ● / —	● / ● / ●	● / ● / —	● / ● / ●	● / ● / ●	● / ● / ●	● / ● / —	● / ● / —
PAL/NTSC PAL/NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
取景器 Viewfinder	 Quad-VGA OLED Tru-Finder	 Quad-VGA OLED Tru-Finder	 UXGA OLED Tru-Finder	 Quad-VGA OLED Tru-Finder	 XGA OLED Tru-Finder	 XGA OLED Tru-Finder	 XGA OLED Tru-Finder	 XGA OLED Tru-Finder	 XGA OLED Tru-Finder	 OLED Tru-Finder	 OLED Tru-Finder	—
液晶显示屏 LCD Monitor	3.0 type (1,440K dots)	3.0 type (1,440K dots)	3.0 type (1,440K dots)	3.0 type (1,440K dots)	3.0 type (1,229K dots)	3.0 type (921K dots)	3.0 type (1,229K dots)	3.0 type (921K dots)	3.0 type (921K dots)	3.0 type (921K dots)	3.0 type (921K dots)	3.0 type (921K dots)
保修 Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty	中国国内保修 Tourist Limited Warranty

^{*1} 拍摄静止影像可扩展到ISO 50-204800。Expandable to ISO 50-204800 for shooting still images. ^{*2} 拍摄静止影像可扩展到ISO 50-102400。Expandable to ISO 50-102400 for shooting still images. ^{*3} 拍摄静止影像可扩展到ISO 204800。Expandable to ISO 204800 for shooting still images. ^{*4} 拍摄静止影像可扩展到ISO 100-102400。Expandable to ISO 100-102400 for shooting still images. ^{*5} 拍摄静止影像可扩展到ISO 100-51200。Expandable to ISO 100-51200 for shooting still images. ^{*6} 3,840 x 2,160像素。3,840x2,160 pixels. ^{*7} 播放HDR动画时,通过USB连接线将本产品连接到兼容HDR(HLG)的索尼电视上播放。Connect to an HDR (HLG) compatible Sony TV via a USB cable when displaying HDR (HLG) movies.





	SEL1635GM	SEL2470GM	SEL135F18GM	SEL85F14GM	SEL1635Z	SEL2470Z	SEL55F18Z	SEL35F18F	SEL70300G	SEL24105G	SEL70200G	SEL1655G	SEL70350G
机型名称 Model Name													
	 MASTER	 MASTER	 MASTER	 MASTER				—					
	FE 16-35mm F2.8 GM	FE 24-70mm F2.8 GM	FE 135mm F1.8 GM	FE 85mm F1.4 GM	Vario-Tessar T* FE16-35mm F4 ZA OSS	Vario-Tessar T* FE24-70mm F4 ZA OSS	Sonnar T* FE 55mm F1.8 ZA	FE 35mm F1.8	FE 70-300mm F4.5-5.6 G OSS	FE 24-105mm F4 G OSS	FE 70-200mm F4 G OSS	E 16-55mm F2.8 G	E 70-350mm F4.5-6.3 G OSS
	E mount	E mount	E mount	E mount	E mount	E mount	E mount	E mount	E mount	E mount	E mount	E mount	E mount
	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	35mm Full Frame	APS-C	APS-C
镜头构成 LENS GROUPS / ELEMENTS	13 綸 16片 13/16	13 綸 18片 13/18	10 綸 13片 10/13	8 綸 11片 8/11	10 綸 12片 10/12	10 綸 12片 10/12	5 綸 7片 5/7	9 綸 11片 9/11	13 綸 16片 13/16	14 綸 17片 14/17	15 綸 21片 15/21	12 綸 17片 12/17	13 綸 19片 13/19
最短摄影距离 MINIMUM FOCUS DISTANCE	0.28m 0.92 ft	0.38m 1.24 ft	0.7m 2.3 ft	0.85m (AF) 0.8m (MF) AF 2.79 ft, MF 2.62 ft	0.28m 0.92 ft	0.4m 1.32 ft	0.5m 1.64 ft	0.22m 0.73 ft	0.9m 2.96 ft	0.38m 1.25 ft	1-1.5m (AF) 1-1.35m (MF) 3.28-4.93 ft (AF)/ 3.28-4.43 ft (MF) ft	0.33m 1.09 ft	1.1-1.5m 3.61-4.93 ft
最大摄影倍率 MAXIMUM MAGNIFICATION RATIO (X)	0.19倍 0.19 x	0.24倍 0.24 x	0.25倍 0.25 x	0.12倍 0.12 x	0.19倍 0.19 x	0.20倍 0.20 x	0.14倍 0.14 x	0.24倍 0.24 x	0.31倍 0.31 x	0.31倍 0.31 x	0.13倍 0.13 x	0.20倍 0.20 x	0.23倍 0.23 x
濾色镜头径 FILTER DIAMETER (MM)	Φ82mm	Φ82mm	Φ82mm	Φ77mm	Φ72mm	Φ67mm	Φ49mm	Φ55mm	Φ72mm	Φ77mm	Φ72mm	Φ67mm	Φ67mm
大小 DIMENSIONS (DIAMETER x LENGTH)	88.5×121.6mm	87.6×136mm	89.5×127mm	89.5×107.5mm	78×98.5mm	73×94.5mm	64.4×70.5mm	65.6×73mm	84×143.5mm	83.4×113.3mm	80×175mm	73×100mm	77×142mm
质量 WEIGHT	680g 24 oz	886g 31.25 oz	950g 33.6 oz	820g 28.92 oz	518g 18.3 oz	426g 15.1 oz	281g 10 oz	280g 9.9 oz	854g 30.2 oz	663g 23.4 oz	840g (不含三脚架安装套环) 29.7 oz (Without tripod mount)	494g 17.5 oz	625g 22.1 oz

机型名称 Model Name		RX1RⅡ	RX1R	RX10Ⅳ	RX100Ⅶ	RX100Ⅵ	RX100Ⅴ	RX100Ⅳ	RX100Ⅲ	RX0Ⅱ	RX0	WX800
		DSC-RX1RM2	DSC-RX1R	DSC-RX10M4	DSC-RX100M7	DSC-RX100M6	DSC-RX100M5A	DSC-RX100M4	DSC-RX100M3	DSC-RX0M2	DSC-RX0	DSC-WX800
					Shooting Grip kit NOW AVAILABLE 		Shooting Grip kit NOW AVAILABLE 			Shooting Grip kit NOW AVAILABLE 		
像素数(约) Effective no. of pixels		42.4 Megapixels	24.3 Megapixels	20.1 Megapixels	20.1 Megapixels	20.1 Megapixels	20.1 Megapixels	20.1 Megapixels	20.1 Megapixels	15.3 Megapixels	15.3 Megapixels	18.2 Megapixels
影像传感器 Image Sensor	类型 Type	 Exmor R™ CMOS Sensor	 Exmor R™ CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor R™ CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor RS CMOS Sensor	 Exmor R™ CMOS Sensor
	尺寸 Size	35 mm Full size	35 mm Full size	1.0 type	1.0 type	1.0 type	1.0 type	1.0 type	1.0 type	1.0 type	1.0 type	1/2.3 type
镜头 Lens												
光学变焦 Optical Zoom		—	—	25x	8.0x	8.0x	2.9x	2.9x	2.9x	—	—	28x
清晰影像缩放功能 Clear Image Zoom		2x	2x ^{*1}	50x(20M) ^{*2}	16x(20M) ^{*3}	16x(20M) ^{*3}	5.8x(20M) ^{*4}	5.8x(20M) ^{*4}	5.8x(20M) ^{*5}	4x(15M) ^{*6}	4x(15M) ^{*6*7}	60x(18M) ^{*8}
视角 Angle of View (相当于35mm规格)(静态图像) (35mm format equivalent) (Still Image)		35 mm	35 mm	24-600 mm	24-200 mm	24-200 mm	24-70 mm	24-70 mm	24-70 mm	24 mm	24 mm	24-720 mm
对焦点 Focus point		399 points(Phase-detection AF) / 25 points(Contrast-detection AF)	25 points	315 points(Phase-detection AF) / 25 points(Contrast-detection AF)	357 points(Phase-detection AF) / 425 points(Contrast-detection AF)	315 points(Phase-detection AF) / 25 points(Contrast-detection AF)	315 points(Phase-detection AF) / 25 points(Contrast-detection AF)	25 points	25 points	25 points	25 points	—
防抖功能 SteadyShot	静态图像 for Still	●	●	●Optical	●Optical	●Optical	●Optical	●Optical	●Optical	—	—	●Optical
	动态影像 for Movie	●EIS (blur reduction)	●EIS (blur reduction)	●Optical (Intelligent Active Mode)	●Optical (Intelligent Active Mode)	●Optical (Intelligent Active Mode)	●Optical (Intelligent Active Mode)	●Optical (Intelligent Active Mode)	●Optical (Intelligent Active Mode)	●Electronical ^{*9}	—	●Optical (Intelligent Active Mode)
显示屏 Monitor	类型 Type	3.0 type (1,229K dots)	3.0 type (1,229K dots)	3.0 type (1,440K dots)	3.0 type (921K dots)	3.0 type (921K dots)	3.0 type (1,229K dots)	3.0 type (1,229K dots)	3.0 type (1,229K dots)	1.5 type (230K dots)	1.5 type (230K dots)	3.0 type (921K dots)
	可折叠液晶屏 Tiltable	● Up 109°, down41°	—	● Up 109°, down41°	● Up 180°, down90°	● Up 180°, down90°	● Up 180°, down45°	● Up 180°, down45°	● Up 180°, down45°	● Up 180°, down90°	—	● Up 180°
取景器 Viewfinder		●	—	●	●	●	●	●	●	—	—	—
动态影像录制模式 Movie Recording Mode		XAVC S, AVCHD, MP4	AVCHD, MP4	 XAVC S, AVCHD	 XAVC S, AVCHD	 XAVC S, AVCHD	 XAVC S, AVCHD	 XAVC S, AVCHD, MP4	XAVC S, AVCHD, MP4	 XAVC S, AVCHD	XAVC S, AVCHD, MP4	 XAVC S, AVCHD
增强自动/智能自动 Auto Mode												
照片效果 Picture Effect	静态图像 for Still	13	13	13	13	13	13	13	13	12	12	13
	动态影像 for Movie	7	7	7	7	7	7	7	7	6	6	7
Wi-Fi/NFC Wi-Fi/NFC		●/●	—/—	●/●	●/●	●/●	●/●	●/●	●/●	●/—	●/—	●/●
PAL/NTSC PAL/NTSC		PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
电池可持续的拍摄张数 ^{*12*13} Battery Continuous Recording Shots		220 shots	220 shots	400 shots	260 shots	240 shots	220 shots	280 shots	320 shots	240 shots	240 shots	370 shots

*1 仅限静态图像。 Still Image only. *2 动画: 4K37.5x/HD50x Movie: 4K37.5x/HD50x *3 动画: 4K12x/HD16x Movie: 4K12x/HD16x *4 动画: 4K4.35x/HD5.8x Movie: 4K4.35x/HD5.8x *5 动画: 5.8x Movie: 5.8x *6 动画: 4K1.5x/HD2x Movie: 4K1.5x/HD2x *7 软件升级3.0 software update 3.0 *8 动画: 4K45x/HD60x Movie: 4K45x/HD60x *9 动画 Movie Only. *10 3,840 x 2,160像素 - 3,840 x 2,160 pixels. *11 播放HDR动画时, 通过USB连接将本产品连接到可兼容HDR (HLG)的索尼电视上播放。 Connect this product to an HDR (HLG) compatible Sony TV via a USB cable to display HDR (HLG) movies. *12 CIPA标准。 CIPA standard. *13 液晶屏处于开启状态。 The LCD screen is turned on.

		FDR-AX700	FDR-AXP55	FDR-X3000RKIT	HDR-AS300RKIT
机型名称 Model Name				 日本限定套装 JAPAN Limited KIT 防溅 Splashproof 防水 Waterproof^{*3} 防尘 Dustproof^{*3} 防震 Shockproof^{*3} 防冻 Freezeproof^{-10°C} 多摄像机控制 Multi Camera Control 立体声麦克风 Stereo Mic ZEISS BIONZ X XAVC S^{*4} 4K 100/60Mbps HD 50Mbps 4K 3,840×2,160 N WiFi CERTIFIED GPS 附带实时监控器和指握手柄的(随机配件)/With Live-view Remote & Finger Grip kit (Supplied Accessories) A B C D E F G H A 实时监控器(RM-LVR3) / Live-View Remote(RM-LVR3) B 皮带 / Belt C 底座适配器 / Mount Adapter D 支架/Cradle E 可重复充电电池(NP-BX1) / Rechargeable Battery Pack(NP-BX1) F 指握手柄(AKA-FGP1) / Finger Grip(AKA-FGP1) G 微型USB电缆 / Micro USB Cable H 水下外壳(MPK-UWH1) / Underwater Housing(MPK-UWH1)	 日本限定套装 JAPAN Limited KIT 防溅 Splashproof 防水 Waterproof^{*3} 防尘 Dustproof^{*3} 防震 Shockproof^{*3} 防冻 Freezeproof^{-10°C} 多摄像机控制 Multi Camera Control 立体声麦克风 Stereo Mic ZEISS BIONZ X XAVC S^{*4} HD 50Mbps N WiFi CERTIFIED GPS
蓝牙™ enabled product Bluetooth® enabled product		—	—	○	○
影像传感器 Image sensor	类型 Type	Exmor RS CMOS Sensor	Exmor R CMOS Sensor	Exmor R CMOS Sensor	Exmor R CMOS Sensor
	尺寸 Size	1.0 type	1/2.5 type	1/2.5 type (7.20mm) back-illuminated	1/2.5 type (7.20mm) back-illuminated
静态图像尺寸 Still Image Size		14.2 Megapixels	16.6 Megapixels	8.2 Megapixels (Approx)	8.2 Megapixels (Approx)
视角 Angle of View		29.0mm	26.8mm ^{*5}	17.0mm	17.0mm
视频信号 Video Signal		PAL / NTSC ^{*6}	PAL ^{*7}	PAL / NTSC ^{*6}	PAL / NTSC ^{*6}
防抖 Image Stabilization		光学稳定拍摄 Optical Steady Shot	平衡光学稳定拍摄 Balanced Optical Steady Shot	平衡光学稳定拍摄 Balanced Optical Steady Shot	平衡光学稳定拍摄 Balanced Optical Steady Shot
光学变焦 Optical Zoom		12x	20x	—	—
清晰影像缩放功能 Clear Image Zoom		Up to 18x (4K) / 24x (HD)	30x (4K) / 40x (HD)	—	—
取景器 Viewfinder		0.39 type OLED / Color 2,359K dots equivalent	0.24 type Color 1,555K dots equivalent	—	—
显示屏 Monitor		3.5 type Xtra Fine LCD display / 1,555K dots	3.0 type Xtra Fine LCD display / 921K dots	—	—

*1 进行XAVC S 4K(100Mbps)录制时需使用SDXC / SDHC存储卡(UHS-3 U3或更高)。进行XAVC S 4K(60Mbps)和XAVC S HD(50Mbps)录制时需使用SDXC / SDHC存储卡(Class 10或更高)。Requires SDXC / SDHC memory card UHS-I U3 or higher for XAVC S 4K(100Mbps) recording, and SDXC / SDHC memory card Class 10 or higher for XAVC S 4K(60Mbps) and XAVC S HD(50Mbps) recording. *2 播放HDR(HLG)动画时,通过USB连接线将本产品连接到可兼容HDR(HLG)的索尼电视上播放。Connect this product to an HDR (HLG) compatible Sony TV via a USB cable to display HDR (HLG) movies. *3 仅当使用MPK-UWH1水下外壳(随机附件)时。Only when used with Underwater Housing MPK-UWH1 (supplied). *4 进行XAVC S HD(50Mbps)和XAVC S 4K(60Mbps)录制时需使用micro SDHC/SDXC Class 10。进行XAVC S 4K(100Mbps)录制时需使用micro SDXC UHS-I U3。micro SDHC / SDXC Class 10 is required for XAVC S HD(50Mbps) and XAVC S 4K(60Mbps) recording, micro SDXC UHS-I U3 is required for XAVC S 4K(100Mbps) recording. *5 当防抖功能设为“标准”或“关闭”时。When Steady Shot is set to “STANDARD” or “OFF”. *6 支持PAL或NTSC制式的电视可输出本相机拍摄的动态影像和静态图像。Movies and still images recorded with this camera can be output by TV that supports PAL or NTSC System. *7 支持PAL制式的电视可输出本相机拍摄的动态影像和静态图像。Movies and still images recorded with this camera can be output by TV that supports PAL System.

	无线头戴式耳机 / Wireless Over Head Band Headphones					真无线耳机 / Truly Wireless Headphones			无线入耳式耳机 / Wireless In-ear style Headphones					
机型 Model	WH-1000XM3	WH-H910N	WH-H810	WH-CH700N	WH-CH510	WF-1000XM3	WF-SP900	WF-SP700N	WI-1000XM2	WI-SP600N	WI-C600N	WI-SP500	WI-XB400	WI-C310
														
降噪 Noise Canceling	●	●	—	●	—	●	—	●	●	●	●	—	—	—
高解析度音频 Hi-Resolution				—	—	—	—	—		—	—	—	—	—
高音质 High Sound Quality					—		—	—		—		—	—	—
重低音 Deep bass	—	—	—	—	—	—	—		—		—	—		—
使用时间 Continuous Playback time	约30小时 Approx.30h (降噪打开) (Noise Canceling ON)	约35小时 Approx.35h (降噪打开) (Noise Canceling ON)	约30小时 Approx.30h	约35小时 Approx.35h (降噪打开) (Noise Canceling ON)	约35小时 Approx.35h	耳机：约6小时 充电盒：约18小时 Headset：Approx.6h Charging Case：Approx.18h (降噪打开) (Noise Canceling ON)	耳机：约3小时 充电盒：约9小时 Headset：Approx.3h Charging Case：Approx.9h (Bluetooth ON) 耳机：约6小时 充电盒：约15小时 Headset：Approx.6h Charging Case：Approx.15h (Bluetooth OFF)	耳机：约3小时 充电盒：约6小时 Headset：Approx.3h Charging Case：Approx.6h (降噪打开) (Noise Canceling ON)	约10小时 Approx.10h (降噪打开) (Noise Canceling ON)	约6小时 Approx.6h (降噪打开) (Noise Canceling ON)	约6.5小时 Approx.6.5h	约8小时 Approx.8h	约15小时 Approx.15h	约15小时 Approx.15h
充电时间 Charging time	约3小时 Approx.3h	约5小时 Approx.5h	约3小时 Approx.3h	约7小时 Approx.7h	约4.5小时 Approx.4.5h	耳机：约1.5小时 充电盒：约3.5小时 Headset：Approx.1.5h Charging Case：Approx.3.5h	耳机：约2.5小时 充电盒：约3.5小时 Headset：Approx.2.5h Charging Case：Approx.3.5h	耳机：约1.5小时 充电盒：约3小时 Headset：Approx.1.5h Charging Case：Approx.3h	约3.5小时 Approx.3.5h	约1.5小时 Approx.1.5h	约2.5小时 Approx.2.5h	约2小时 Approx.2h	约3小时 Approx.3h	约3小时 Approx.3h
防水等级 Waterproof	—	—	—	—	—	—	IPX5/8防水等级 IPX5/8 Waterproof	IPX4级防泼溅 IPX4 Splash-proof	—	IPX4级防泼溅 IPX4 Splash-proof	—	IPX4级防泼溅 IPX4 Splash-proof	—	—
防尘等级 Dustproof	—	—	—	—	—	—	IP6X防尘等级 IP6X Dustproof	—	—	—	—	—	—	—
支持的编解码器 Bluetooth Cordec	SBC/AAC/LDAC /aptX/aptX HD	SBC/AAC/LDAC	SBC/AAC/LDAC	SBC/AAC /aptX/aptX HD	SBC/AAC	SBC/AAC	SBC/AAC	SBC/AAC	SBC/AAC/LDAC	SBC/AAC	SBC/AAC /aptX	SBC/AAC	SBC/AAC	SBC/AAC
内存容量 Built-in memory	—	—	—	—	—	—	4GB	—	—	—	—	—	—	—
质量 Weights	约255g Approx.255g	约251g Approx.251g	约180g Approx.180g	约240g Approx.240g	约132g Approx.132g	耳机：约8.5g×2 充电盒：约77g Headset：Approx.8.5g×2 Charging Case：Approx.77g	耳机：约7.3g×2 充电盒：约75g Headset：Approx.7.3g×2 Charging Case：Approx.75g	耳机：约7.6g×2 充电盒：约45g Headset：Approx.7.6g×2 Charging Case：Approx.45g	约58g Approx.58g	约21g Approx.21g	约34g Approx.34g	约18g Approx.18g	约21g Approx.21g	约19g Approx.19g
包装清单 Supplied accessories	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携盒 Carrying case •用于飞机上的插头转接器 Plug adapter for in-flight use	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m) •便携袋 Carrying pouch	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m)	•Micro-USB连接线 (约50 cm) Micro-USB cable (approx. 50 cm) •耳机连接线(约1.2 m) Headphone cable (approx. 1.2 m)	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •混合硅胶耳塞 (S/S/M/L/LL每种尺寸2个) Long Hybrid silicone rubber earbuds (SS/S/M/L 2 each) •三重舒适耳塞 (S/M/L/LL每种尺寸2个) Triple-comfort earbuds (S/M/L 2 each) •充电盒 Charging case	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •混合硅胶耳塞 (S/S/M/L/LL每种尺寸2个) Hybrid silicone rubber earbuds (S/S/M/L/LL 2 each) •游泳耳塞 (S/M/L/LL每种尺寸2个) Swimming earbuds (S/M/L/LL 2 each) •弧形撑架 (S/M/L/LL每种尺寸2个) Arc supporters (M/L 2 each) •系绳 Leash cord •充电盒 Charging case	•Micro-USB连接线 (约50 cm) Micro-USB cable (approx. 50 cm) •加长型混合硅胶耳塞 (SS/S/M/L每种尺寸2个) Long Hybrid silicone rubber earbuds (SS/S/M/L 2 each) •弧形撑架 (M/L每种尺寸2个) Arc supporters (M/L 2 each) •充电盒 Charging case	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •耳机连接线(约1.0 m) Headphone cable (approx. 1.0 m) •便携盒 Carrying case •混合硅胶耳塞 (SS/S/M/L各2个) Hybrid silicone rubber earbuds (SS/S/M/L 2 each) •三重舒适耳塞 (S/M/L各2个) Triple-comfort earbuds (S/M/L 2 each) •用于飞机上的插头转接器 Plug adaptor for in-flight use	•Micro-USB连接线 (约50 cm) Micro-USB cable (approx. 50 cm) •加长型混合硅胶耳塞 (SS/S/M/L每种尺寸2个) Long Hybrid silicone rubber earbuds (SS/S/M/L 2 each) •弧形撑架 (M/L每种尺寸2个) Arc supporters (M/L 2 each)	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •加长型混合硅胶耳塞 (SS/S/M/L每种尺寸2个) Long Hybrid silicone rubber earbuds (SS/S/M/L 2 each)	•Micro-USB连接线 (约50 cm) Micro-USB cable (approx. 50 cm) •携带架 Carrying holder •耳机耳塞 (S/M每种尺寸2个) Ear tips (S/M 2 each)	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •混合硅胶耳塞 (S/M/L每种尺寸2个) Hybrid silicone rubber earbuds (S/M/L 2 each)	•USB Type-C™连接线 (USB-A至USB-C™) (约20 cm) USB Type-C™ cable (USB-A to USB-C™) (approx. 20 cm) •混合硅胶耳塞 (S/M/L每种尺寸2个) Hybrid silicone rubber earbuds (S/M/L 2 each)	

SONY		Walkman® Specifications / MP3播放器规格				WALKMAN®		Sony Overseas Models	
Model Name 机型名称	NW-WM1Z	NW-WM1A	NW-A55	NW-WS623	NW-E394	NWZ-B183F			
	   *1	   *1	    *1	   *1					
Capacity 容量	256GB	128GB	16GB	4GB	8GB	4GB			
Colors 颜色	Gold	Black	Moonlit Blue / Twilight Red / Pale Gold / Grayish Black / Horizon Green	Black / Grayish White / Blue / Lime Green	Black / Blue / Red	Gold / Blue / Red / Pink			
Usage 用途	Music	Music	Music / FM	Music	Music / Photo / FM	Music / FM / Rec (FM)			
FM Tuner FM调频	—	—	● (87.5 to 108.0 MHz)	—	● (87.5 to 108.0 MHz)	● (87.5 to 108.0 MHz)			
φ4.4mm Balanced Connection φ4.4mm平衡连接	●	●	—	—	—	—			
Audio Formats(Codec) 音频格式(编解码器) *2	MP3 / WMA / Linear PCM / AAC / HE-AAC / FLAC*3 / Apple Lossless*3 / AIFF*3 / DSD*4	MP3 / WMA / Linear PCM / AAC / HE-AAC / FLAC*3 / Apple Lossless*3 / AIFF*3 / DSD*4	MP3 / WMA / AAC / HE-AAC / FLAC*3 / WAV*3 / Apple Lossless*3 / AIFF*3 / DSD*4 / APE / MQA	MP3 / WMA / AAC / Linear PCM / FLAC*3	MP3 / WMA / AAC / Linear PCM	MP3 / WMA			
Photo Format(Codec) 照片格式(编解码器) *5	—	—	—	—	JPEG	—			
Display 显示	4.0-inch, TFT color display FWVGA(854x480)	4.0-inch, TFT color display FWVGA(854x480)	3.1 inch, TFT color display, WVGA(800x480)	—	1.77 inch, TFT color display	0.9 inch, OLED			
Dimensions(WxHxD)(Approx.) 尺寸(宽x高x深)(约)	72.9×124.2×19.9mm	72.9×124.2×19.9mm	55.7×97.3×10.8mm	—	43.2×92.3×9.6mm	84.8×23.6×15.3mm			
Mass(Approx.) 重量(约)	455g	267g	99g	32g	39g	30g			
Playback Time(Approx.) 播放时间(约)	Music: 33 hours*6	Music: 33 hours*6	Music: 45 hours*6*7	Music: 12 hours*6*8	Music: 35 hours*6	Music: 20 hours*6			
USB-based Charging Time(Approx.) USB充电时间(约)	7 hours (Built-in Lithium-ion Battery)	7 hours (Built-in Lithium-ion Battery)	4 hours (Built-in Lithium-ion Battery)	1.5 hours (Built-in Lithium-ion Battery)	2 hours (Built-in Lithium-ion Battery)	70 minutes (Built-in Lithium-ion Battery)			
System Requirements Computer 系统要求电脑	Windows / Mac	Windows / Mac	Windows / Mac	Windows / Mac	Windows / Mac	Windows			
3minutes Charge 3分钟充电	—	—	—	Up to 60minutes play back (MP3 128kbps)	—	Up to 90minutes play back (MP3 128kbps)			
Menu Display Language 多语言菜单显示	English / German / Spanish / French / Italian / Polish / Portuguese / Russian / Turkish / Korean / Japanese / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / German / Spanish / French / Italian / Polish / Portuguese / Russian / Turkish / Korean / Japanese / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / German / Spanish / French / Italian / Polish / Portuguese / Russian / Turkish / Korean / Japanese / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	—	English / German / Spanish / French / Italian / Polish / Portuguese / Russian / Turkish / Japanese / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / German / Spanish / French / Portuguese / Russian / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)			
Instruction Manual Language 使用说明书	English / Arabic / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / Arabic / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / Arabic / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / Arabic / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / Arabic / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)	English / Arabic / Korean / Chinese (Traditional Chinese / Simplified Chinese) 中文 (繁体中文 / 简体中文)			
Warranty 保修	Tourist Limited Warranty 国际保修 (52个国家和地区)	Tourist Limited Warranty 国际保修 (52个国家和地区)	Tourist Limited Warranty 国际保修 (52个国家和地区)	Tourist Limited Warranty 国际保修 (52个国家和地区)	Tourist Limited Warranty 国际保修 (52个国家和地区)	Tourist Limited Warranty 国际保修 (52个国家和地区)			

*1 This product recognizes audio sources exceeding CD quality (44.1 kHz/16 bit quantization) and DAT quality (48 kHz/16 bit quantization) as High-resolution Audio.The "HR" symbol is displayed for high-resolution audio sources. (本产品使用超过CD (44.1kHz采样, 16位量化) 和DAT规格 (48kHz采样, 16位量化) 的声源作为高信息量音声源。显示高信息量音声源的"HR"标记) *2 Copyright protected files cannot be played back. Sampling frequency may not correspond to all encoders. Files that are 4 GB (APE is 2GB) or larger cannot be played back. (不会播放受著作权保护的文件。 Contents are valid as of October 2018. 有关支持的音频文件的比特率和采样频率等信息, 请参考产品说明书。 大于4GB的文件 (APE仅2GB) 无法播放。) *3 For sampling frequency over 352.8 kHz, it will be down convert playback. (它将在352.8kHz以上进行下转换播放) *4 Audio that is converted to Linear PCM is output. (将播放转换为LPCM。) *5 Some photo files cannot be played back, depending on their file formats. (根据文件格式的不同, 某些照片文件无法重放。) *6 When playing MP3 128kbps. (当播放MP3 128kbps时。) *7 Noise Canceling: OFF. (降噪:关闭。) *8 Ambient sound function: OFF. (环境声模式:关闭。)

SONY

Wireless Speaker Specifications / 无线个人扬声器规格表



Model 机型	hear go 2 SRS-HG10	SRS-XB32	SRS-XB22	SRS-XB12
Speaker System 扬声器系统	2ch Passive radiator	2ch Passive radiator	2ch Passive radiator	Monaural Passive radiator
Speaker Add Function 扬声器添加功能	● (Stereo/Double)	● (Stereo/Double)	● (Stereo/Double)	● (Stereo/Double)
无线上网	●	—	—	—
Bluetooth® 蓝牙	●	●	●	●
NFC 一触连接	●	●	●	—
LDAC ※1	●	●	●	—
EXTRA BASS	●	●	●	●
Hands-Free Function 免提	●	●	●	●
Water-proof / Dust-proof 防水 / 防尘	—	● ※2	● ※2	● ※2
Lighting 灯光	—	● Multi Color Lighting and strobe	● Single Color Lighting	—
Party Booster 派对炫音功能	—	●	●	—
Battery Life (Approx.) 电池寿命 (约)	12h Battery Charging Time : 5h	24h Battery Charging Time : 5h	12h Battery Charging Time : 4h	16h Battery Charging Time : 4.5h
USB Charge USB充电	●	●	●	●
Dimensions(W×H×D):mm (Approx.) 尺寸(宽×高×深) (约)	204×62×60	238×85×83	201×72×68	Φ74×92
Weights (Approx.) 重量 (约)	700g	900g	540g	243g
Instruction Manual Language 使用说明书	English Only	English/Chinese(Traditional) 中文/ Korean/Thai/Arabic	English/Chinese(Traditional) 中文/ Korean/Thai/Arabic	English/Chinese(Traditional) 中文/ Thai/Arabic/Indonesian
Warranty 保修	Tourist Limited Warranty 中国国内保修	Tourist Limited Warranty 中国国内保修	Tourist Limited Warranty 中国国内保修	Tourist Limited Warranty 中国国内保修

※1 High quality wireless audio with 3x the data transmitted via Bluetooth. 数据传输速度几乎是传统Bluetooth®(音频的三倍,为您带来出众的无线聆听体验。) ※2 Applicable: fresh water, tap water, perspiration, pool water Not applicable: liquids other than those above (examples: soapy water, detergent water, water with bath agents, shampoo, hot spring water, seawater, etc.) 适用于:淡水,自来水,汗水,池水 不适用于:上述以外的其他液体(例如 肥皂水,清洁剂水,含沐浴剂,洗发精的水,温泉水,海水等)

Contents are valid as of May 2019.